

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
3 January 2002 (03.01.2002)

PCT

(10) International Publication Number  
**WO 02/01691 A1**

(51) International Patent Classification<sup>7</sup>: **H02H 3/00**,  
3/16, 3/32, 9/08

(74) Agents: **REIN, Barry, D. et al.**; Pennie & Edmonds LLP,  
1155 Avenue of the Americas, New York, NY 10036 (US).

(21) International Application Number: **PCT/US01/20323**

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(22) International Filing Date: 26 June 2001 (26.06.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09/603,069 26 June 2000 (26.06.2000) US  
09/670,842 27 September 2000 (27.09.2000) US

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant: **PREMIER AVIATION, INC.** [US/US]; 2621  
Aviation Parkway, Grand Prairie, TX 75052 (US).


Published:

— with international search report

(72) Inventors: **LANGFORD, Joseph, Andrew**; P.O. Box 382106, Duncanville, TX 75138 (US). **OSBORNE, Gregory, Warren**; 12012 Quail Run Drive, Mansfield, TX 76063 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **METHOD AND APPARATUS FOR DETECTING ELECTRICAL FAULTS AND ISOLATING POWER SOURCE FROM THE ELECTRICAL FAULTS**



(57) Abstract: The present invention is a method and apparatus for protecting a power supply (200) from electrical faults. The present invention operates substantially independently of the current drawn by the load (300). In addition, the present invention includes a time delay circuitry (500) for preventing false detection of ground faults when the power source is connecting to the load. In a preferred embodiment, the apparatus (20) of the present invention includes a control circuitry (100) for connecting the power supply (200) to the load (300). The apparatus (20) also preferably includes a sensor circuitry (600) for detecting electrical faults, including ground, transient, and arc faults, and triggering the control circuitry (100) to disconnect the power source from the electrical faults when electrical faults are detected. Thus, the present invention can protect wiring and load connections from improper operation and fire hazards that may be caused by electrical faults. Finally, the apparatus preferably includes a fault protection condition indicator (514) to indicate whether the circuit breaker circuitry is working properly.

WO 02/01691 A1